

TECHNICAL DATA SHEET

PRODUCT NAME: FP-45

Nº CAS: 64742-47-8

NUMBER UN: 1268

DESCRIPTION: Aliphatic solvent. Distillates (Petroleum).

SPECIFICATIONS

PHYSICOCHEMICAL PARAMETER	MIN	MAX	METHOD
SAYBOLT COLOR	+28	N/A	ASTM D-6045
SPECIFIC GRAVITY (25°C)	0,78	0,82	ASTM D-1298
DISTILLATION			
Initial Boiling Point (IBP)°C	160	N/A	ASTM-D-86
Final Point (FP)°C	N/A	230	ASTM-D-86
FLASH-POINT (°C)	>45	N/A	ASTM D-93
WATER (ppm)	N/A	100	ASTM D-6749
VISCOSITY (cst @ 40 °C)	0.8	N/A	ASTM D-445
SULFUR CONTENT (ppm)	N/A	20	ASTM D-5453
AROMATICS (% Vol)	N/A	1	ASTM D-6591

Applications: Used in surface cleaners (wood and formica) .Base for industrial lubricants in textile machineries and / or food processing. Industrial degreasers.

Elaboration Date: 01-2015	LastReview Date: 06-2018	Designed By: Lab Quality Analyst	Approved By: Technical Director
-------------------------------------	------------------------------------	--	---